

Broadband High Power Amplifier

Product Name : RCA2030H44E, Code Name : B8Y6SD3UN44

Doc. Name : Preliminary Short Spec.

<p style="text-align: center;">Preliminary Short Specification for RCA2030H44E</p>
--

1

<p style="text-align: center;">RESTRICTION ON USE, DUPLICATION, OR DISCLOSURE OF PROPRIETARY INFORMATION</p>

This document contains proprietary information, which is the sole property of RFcore co., LTD.
The document is submitted to the recipient for his use only.
By receiving this document the recipient undertakes not to duplicate the documents or to disclose in part of, or the whole of, any of the information contained herein to any third party without receiving before hand, written permission from the submitting company.

Created	Printed	Document Number	Revision	Manufacturer
2014/6/23	2017/2/6		B	RFcore co.,Ltd
File : RCA2030H44E Short Spec.docx				

The Specifications is subject to change before finalization

Customer Service: Tel. 82-31-708-7575

Email: sales@rfcore.com

<http://www.rfcore.com>

Broadband High Power Amplifier

Product Name : RCA2030H44E, Code Name : B8Y6SD3UN44

Doc. Name : Preliminary Short Spec.

ELECTRICAL SPECIFICATIONS		@ 50 Ohms load, 28 Vdc, Tc = 35 °C
Parameter	Specification	Remark
Frequency Range	2000 ~ 3000 MHz	
Saturated Output Power	44 dBm min.	@ CW
Small Signal Gain	44 dB min.	Input Level = - 15 dBm
Gain Flatness	Peak to Peak 4 dB	Input Level = - 15 dBm
Maximum Input Power for no damage	7 dBm	
Input VSWR	Less than 2 : 1	
Maximum load VSWR for amplifier working	3.5 : 1	Works with degraded performance.
Maximum load VSWR for amplifier survival	Infinite, all phase	If VSWR fail alarm is activated, the gain of the amplifier will be reduced to protect itself.
Enable/Disable Switching Time	2 usec typ.	
DC Input Voltage	28 ± 1.0 Vdc	
Current Consumption	2.8A typ., 3.5 A max.	@ Pout = 44 dBm
RF Input Signal Format	CW	

2

Interface Pin Description		
Connector	Description	Specification
I/O Interface(D-Sub 9Pin Male)	1. Enable(Active Low)	Pulled-up @ 5V with 10kohm
	2. Forward Power Monitor	Logarithmic Detector(0.05V/dB)
	3. VSWR Fail Alarm	TTL HIGH(5V) @ high VSWR VSWR alarm will be activated a certain ratio between 3.5 and infinite VSWR. The alarm is not latched signal.
	4. Reflected Power Monitor	Logarithmic Detector(0.05V/dB)
	5. Temperature Monitor	VT= 10(mV) * Tc(°C) + 500(mV), Tc = Case Temperature ± 5°C
	6. Vcc	
	7. Vcc	
	8. GND	
	9. GND	

Created	Printed	Document Number	Revision	Manufacturer
2014/6/23	2017/2/6		B	RFcore co.,Ltd
File : RCA2030H44E Short Spec.docx				

The Specifications is subject to change before finalization

Customer Service: Tel. 82-31-708-7575

Email: sales@rfcore.com

http://www.rfcore.com

Broadband High Power Amplifier

Product Name : RCA2030H44E, Code Name : B8Y6SD3UN44

Doc. Name : Preliminary Short Spec.


ENVIRONMENTAL SPECIFICATIONS

Parameter	Specification	Remark
Operating Case Temperature	-20 ~ +70 °C	
Storage Temperature	-40 ~ +85 °C	

MECHANICAL SPECIFICATIONS

Parameter	Specification	Remark
Dimension	145 * 95 * 25 mm	
Weight	Less than 530 g	
Input Connector	SMA Female	
Output Connector	SMA Female	
Control Connector	D-Sub 9Pin Male	
Cooling	Adequate Heat-sink required	

MECHANICAL DRAWING



DRAWING REFERNECE: This is subject to change without notice.

Created	Printed	Document Number	Revision	Manufacturer
2014/6/23	2017/2/6		B	RFcore co.,Ltd
File : RCA2030H44E Short Spec.docx				

The Specifications is subject to change before finalization

Customer Service: Tel. 82-31-708-7575

Email: sales@rfcore.com

http://www.rfcore.com